



Weatherproof to IP44
External Camera

Colour / BW
Splashproof Camera



Extension Kit

Camera Range

- * **Simple to Install**
- * **Day and Night Use**
- * **Internal and External Installation**

Product Description

Black and White Splash-proof Camera with 10 metres of white cable including ready made RJ11 connector.

Colour Splash-proof Camera with 10 metres of white cable including ready made RJ11 connector.

Weatherproof to IP44 External Camera with 20 metres of white cable including ready made RJ11 connector.

Extension Kit: 20 metres of white cable with a pre-terminated RJ11 connector on one end and an RJ11 socket on the other end.

| Specification | Black & White | Colour | Weatherproof |
|------------------------------|------------------------------------|---------------------------------|------------------------------------|
| Imager | 1/3" CMOS image sensor | 1/3" CMOS image sensor | 1/3" CMOS image sensor |
| Scanning | 2:1 Interface | 2:1 Interface | 2:1 Interface |
| Shutter | 1/60 to 1/10,000sec | 1/60 to 1/15,000sec | 1/60 to 1/10,000sec |
| Video Output | 1v p-p Comp. video 75 ohm | 1v p-p Comp. video 75 ohm | 1v p-p Comp. video 75 ohm |
| Picture Element | (H) 352 x (V) 288 = 101, 376 pixel | (H) 628x (V) 528= 365,496 pixel | (H) 352 x (V) 288 = 101, 376 pixel |
| Min Illumination | 3 @ f1.20 | 3 @ f1.20 | 3 @ f1.20 |
| Resolution | 300 TV lines (min) | 380 TV lines (min) | 300 TV lines (min) |
| Signal to Noise Ratio | >42 db (AGC on) | >45 db (AGC on) | >42 db (AGC on) |
| Operating Temperature | -10C to 55C | -10C to 55C | -10C to 55C |
| Humidity Limits | 0-95% | 0-95% | 0-95% |
| Lens | 3.8mm, f2.0, FOV 74 x 54 std | 5.2mm, f2.2, FOV 92x 54 std | 3.8mm, f2.0, FOV 74 x 54 std |
| Operating Voltage | 9 - 14V DC | 9 - 14V DC | 9 - 14V DC |
| Current Consumption | <18mA. | <35mA. | <18mA. |
| Indoor or Outdoor | Indoor | Indoor | Outdoor |
| Spectrum | B/W | Colour | B/W |
| Housing | Plastic | Plastic | Metal |